

Technical Specifications	Pantum P3255DN/P3225DN
	
Printing	
Technology	Monochrome laser
Print speed (black)	35ppm
First print out time	Less than 8.5s
Maximum monthly volume	50,000 pages
Resolution(dpi)	Max.1200×600dpi
Printer language	PCL6,PCL5e,PS3
Duplex Mode	Automatic
Paper handling	
Paper input	250 pages input tray 1page multipurpose tray
Paper output	150 pages
Media type	Plain, Thick, Transparency, Cardstock, Label, Envelope
Media size	A4,A5,A6,JIS B5,ISO B5,B6, Letter, Legal, Executive,Statement, Monarch envelope, DL envelope,C5 envelope,C6 envelope,NO.10 envelope, Japanese Postcard,Folio,Oficio,Big 16k, 32k,16k,Big 32k,
Media weight	60~105g/m ² input tray 60~200g/m ² multipurpose tray
General specs	
Dimensions (W×D×H)	370mm× 370mm× 270mm (14.6" × 14.6" × 10.6")
Display	LED
Weight (w/o cartridges)	9kg(19.8lb)
Recommended environment	Recommended temperature : 10-32°C(50°F-90°F)
	Recommended humidity : 20% - 80%

Power	110V Model : AC110~127V(±10%);50Hz/60Hz(±2Hz);8A 220V Model : AC220~240V(-15%,+10%),50Hz/60Hz(±2Hz);4A
Noise	Printing : Less than 55dB Standby : Less than 30dB
Power consumption	Printing: Average 495W Ready: 50W Sleep Mode:3.5W
Operating system compatibility	Microsoft Windows Server2003/Server2008/Server2012/XP/Vista/Win7/Win8 Mac OS X 10.4/10.5/10.6/10.7/10.8 Ubuntu 12.04LTS
Connectivity	Hi-speed USB2.0, 10/100Base-Tx Ethernet
Processor	350MHz
Memory	128MB RAM
Consumable*	
Starter	3000 pages
Standard capacity	3000 pages(PB-310)
High capacity	6000 pages(PB-310H)