

USB 3.0 to HDMI® External Multi Monitor Video Graphics Adapter for Mac® & PC – DisplayLink™ Certified – HD 1080p

StarTech ID: USB32HDPRO



The USB32HDPRO USB 3.0 to HDMI Adapter lets you add an HDMI display to your computer through a USB 3.0 port, providing a cost-effective and convenient way to expand the video capabilities of your Mac® or PC computer system.

USB 3.0 Bandwidth, High Definition Performance

With USB 3.0 support, this external video adapter delivers the bandwidth needed for accelerated High-Definition video performance, capable of outputting video resolutions up to 1920x1200 / 1080p. Even if your current computer doesn't have a USB 3.0 port available, the USB32HDPRO is backward compatible with USB 2.0, so you'll be able to connect your HDMI monitor to your computer and be ready for when you upgrade to a USB 3.0-equipped system.

Easier Multitasking, More Productivity

Add the screen space you need to simplify multitasking and maximize productivity, without even opening your computer case. Some computer systems, including MacBook® and Ultrabook™ laptops and small form-factor desktops, are too compact to install an internal video card. A USB display adapter offers an easy workaround, performing as an external video card that only requires an available USB port to mirror or extend your desktop onto another display.

DisplayLink Plug-and-Display Certified

Installation has never been easier. When you connect this DisplayLink Plug and Display certified adapter to a web-enabled Windows® 7 or Windows® 8 computer, it automatically downloads and installs the most up-to-date drivers for you, so you won't have to manually download or install any software.

The USB32HDPRO is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Recommended System Requirements:

CPU: Quad Core 2.4GHz or Higher (i5 recommended)

RAM: 4GB or higher

Applications

- Add a secondary DisplayPort display and extend your desktop, without taking apart your computer to install a new video card
- Add multi-monitor capability to a single computer, to enhance multimedia presentations
- Great for researchers and writers, offering the ability to have reference material on one display while working on a separate document on another
- Increase productivity by running multiple applications on different screens - check your email on one display and search the web on the other
- View large or several spreadsheets across multiple displays
- A compact, lightweight solution for traveling business associates using USB 3.0-capable laptop PCs, enabling connection to a secondary display/projector
- Add an additional video output to computer systems with no room for expansion, such as laptops, ultrabooks, MacBooks, and compact form factor desktops (point of sale workstations)

Features

- USB 3.0 host connection provides maximum bandwidth for superior performance
- Increase productivity by mirroring or extending your desktop onto another display
- DisplayLink Plug and Display certified - automatic driver installation and updates
- Works with Mac® & PC
- USB-powered - No external power adapter required
- Supports 5.1 channel audio
- Supports video resolutions up to 1920x1200 / 1080p
- Backward compatible with USB 2.0

Technical Specifications

Warranty	2 Years
Audio	Yes
Chipset ID	DisplayLink - DL3500
Memory	512MB DDR II
Output Signal	HDMI
USB Pass-Through	No
Audio Specifications	5.1-Channel Surround (48Khz)
Maximum Digital Resolutions	1920x1200 / 1080p
Note	If using OS X 10.8, Apple update 10.8.3 must be installed before installing DisplayLink software. 10.8.3 fixes several serious OS X bugs exposed when DisplayLink software is installed.
Supported Resolutions	Widescreen(16/32 bit): 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720 Standard(16/32 bit): 1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600
Wide Screen Supported	Yes
Connector A	1 - USB 3.0 A (9 pin; SuperSpeed) Male
Connector B	1 - HDMI (19 pin) Female
OS Compatibility	Windows® 8/8.1 (32/64bit), 7 (32/64bit), Vista(32/64), XP(32/64), 2000 (Aero 3D interface supported) Apple® OSX Yosemite (10.10), Mavericks (10.9) Mountain Lion (10.8), Lion (10.7), Snow Leopard (10.6)
System and Cable Requirements	1~2 USB Displays Office Application: CPU: i3 Dual core 2.8GHz RAM: 2GB or higher Full HD Video: CPU: Quad Core 2.4GHz or Higher (i5 recommended) RAM: 4GB or higher
System and	Not intended for gaming

Cable Requirements	
Cable Length	3 ft [0.9 m]
Color	Black
Enclosure Type	Plastic
Product Height	0.8 in [20 mm]
Product Length	3.5 in [90 mm]
Product Weight	2.1 oz [59 g]
Product Width	2.2 in [55 mm]
Power Source	USB-Powered
Humidity	20°C to 80°C (68°F to 176°F)
Operating Temperature	0°C to 35°C (32°F to 95°F)
Storage Temperature	-5°C to 40°C (23°F to 104°F)
Shipping (Package) Weight	0.5 lb [0.2 kg]
Included in Package	1 - USB 3.0 to HDMI Adapter
Included in Package	1 - Software installation disc
Included in Package	1 - Instruction Manual

Certifications, Reports and Compatibility

