

## HDMI Over IP Extender - 1080p

Product ID: IPUSB2HD3



This HDMI over IP extender lets you share an HDMI display or projector with the wireless or wired computer on your network. With intuitive controls and effortless screen sharing, this extender makes it easier than ever for users to collaborate and deliver presentations in boardrooms and office meetings.

The IP video extender supports resolutions up to 1080p and features two built-in USB ports, enabling you to connect remote USB devices to your computer from your display. It's the perfect solution for controlling a computer from wherever the adapter is located.

### Streamline your digital collaboration

The IP video extender helps you boost your office productivity, by making it easier for users to collaborate and communicate. The included software lets you connect multiple computers and easily switch between which user is sharing their content with the HDMI display, unlike some wireless video systems that are difficult to configure and require users to disconnect and reconnect manually. You can even use the video-over-IP extender to share information with a remote audience, such as connecting to a remote display over an office LAN, to hold remote meetings while you're in another part of the office.

## **Bring your own device**

With this IP video extender, you can turn your HDMI television, monitor or projector into an IP display that can connect to any Windows® computer on your network, making it perfect for conference rooms and classrooms where different ideas are shared by users who bring their own computers.

## **Extend two USB devices at your display**

With a built-in USB hub, you can use your computer to access two remote USB devices at your remote display, enabling you or your customers to control the computer from the remote location. Remote operation can be used to create interactive digital signage, to engage your customers. Or, if you're using the video-over-IP extender as part of your IT infrastructure, you can use the USB extender to add a remote KVM console that you can use to control your server from a remote location.

The IPUSB2HD3 is backed by a 2-year StarTech.com warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Enable your employees or co-workers to share each other's screens on a boardroom display
- Create a remote KVM console that you can use to control your server from a remote location
- Share information with clients at doctors offices and hospitals, while keeping the computer in a remote, secure location

### Features

- Collaborate with co-workers by using your network to easily switch between devices shown on a shared display
- Share video with a wireless or wired LAN connection using any Windows computer on your network
- Control the video-over-IP adapter, using the included software
- Built-in 2-port USB hub
- Supports resolutions up to 1080p

<b>Hardware</b>	Warranty	2 Years
	Audio	Yes
	Chipset ID	DisplayLink - DL195
	Daisy-Chain	No
	Output Signal	HDMI
	Ports	1
<b>Performance</b>	Audio Specifications	Two channel stereo audio supported
	General Specifications	This USB video adapter uses a DisplayLink family chipset. If you're connecting this device to a computer along with additional USB video adapters or docking stations, please avoid using devices with a Trigger or Fresco family chipset.
	Max Distance	100 m / 330 ft
	Maximum Data Transfer Rate	USB - 480Mbps Ethernet - 1000Mbps
	Maximum Digital Resolutions	1920x1080
	Supported Resolutions	<b>Widescreen (16/32 bit):</b> 1920x1200, 1920x1080, 1680x1050, 1600x900, 1440x900, 1360x768, 1280x800, 1280x768, 1280x720  <b>Standard(16/32 bit):</b> 1600x1200, 1400x1050, 1280x1024, 1280x960, 1152x864, 1024x768, 800x600
	Wide Screen Supported	Yes
<b>Connector(s)</b>	Connector A	1 - HDMI (19 pin) Female Output 2 - USB A (4 pin) Female
	Connector B	1 - USB B (4 pin) Female 1 - RJ-45 Female
<b>Software</b>	OS Compatibility	Windows® 10, 8.1, 8, 7, Vista, XP
<b>Power</b>	Center Tip Polarity	Positive
	Input Current	0.6 A
	Input Voltage	100 ~ 240 AC
	Output Current	2 A
	Output Voltage	5 DC
	Power Consumption (In Watts)	10
	Power Source	AC Adapter Included

<b>Physical Characteristics</b>	Color	Black
	Enclosure Type	Aluminum
	Product Height	0.9 in [24 mm]
	Product Length	4 in [102 mm]
	Product Weight	10.7 oz [304 g]
	Product Width	2.9 in [74 mm]
<b>Packaging Information</b>	Shipping (Package) Weight	25.1 oz [710 g]
<b>What's in the Box</b>	Included in Package	1 - HDMI over IP extender
		1 - USB cable
		1 - CAT5 cable
		1 - universal power adapter (NA, EU, UK, ANZ)
		1 - mounting bracket
		1 - mounting screw kit
		1 - rubber foot set
		1 - quick start guide

Product appearance and specifications are subject to change without notice.