

## Key Features

5,200 Lumen Brightness | Vertical/Horizontal Lens Shift with Centered Lens | Stackable Design | 360-degree Installation  
| SuperColor: Amazing Color Accuracy



## Product Description


Bright and versatile for any professional installation, the ViewSonic® Pro9520WL WXGA projector delivers everything you need for big screens in big venues. Delivering 5,200 lumens of advanced high brightness, this projector is ideal for auditoriums, large boardrooms, houses of worship, and more. Thanks to SuperColor™ technology, content is brought to life with captivating color, crisp graphics, and stunning videos no matter the environment. Designed for installers, this top-notch performer is also easy to deploy and manage with its wide 1.7x optical zoom adjustment, a centered lens design, and a vertical/horizontal lens shift feature that provides extreme flexibility in even the most challenging installations. Thanks to the stackable design of these projectors, light output can be doubled by simply placing one projector on top of the other - perfect for large venues with high ambient light.



- |                           |                         |                 |
|---------------------------|-------------------------|-----------------|
| 01. Menu Controls         | 06. Focus ring          | 11. Monitor Out |
| 02. Zoom Ring             | 07. Vertical Lens Shift | 12. DVI-D       |
| 03. Horizontal Lens Shift | 08. IR Remote Sensor    | 13. HDMI In     |
| 04. Lamp Access           | 09. Projection Lens     | 14. HDMI/MHL In |
| 05. Elevation Feet        | 10. VGA (x2)            | 15. RS232       |




- |                         |                    |                          |                   |
|-------------------------|--------------------|--------------------------|-------------------|
| 16. Power Cable Lock    | 21. Mic In         | 26. PC Audio In          | 31. Audio Out     |
| 17. AC In               | 22. LAN            | 27. IR In/Out            | 32. RCA Audio Out |
| 18. Video/S-Video In    | 23. USB 2.0 Type A | 28. 12V DC Trigger       | 33. RCA Audio In  |
| 19. Wired Remote In/Out | 24. 3D VESA        | 29. Kensington Lock Slot |                   |
| 20. USB Service Port    | 25. BNC In         | 30. Security Bar         |                   |



1280 x 800  
**RESOLUTION**



5,200  
**LUMENS**



1.32 - 2.24:1  
**THROW RATIO**

## Contact Sales

- call: 888.881.8781
- email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)
- visit: [viewsonic.com](http://viewsonic.com)

**Display:**

Throw Distance:	3.3 - 55.8 ft / 1 - 17m
Throw Ratio:	1.32 - 2.24:1
Type:	DLP
Lens:	1.7x Manual optical zoom / manual optical focus
Lens Shift:	Vertical (-12.7%/+23.7%) / Horizontal (+/- 10.9%)
Keystone:	Vertical ( $\pm 30^\circ$ ) / Horizontal ( $\pm 30^\circ$ )
Light Source (watt):	370
Light Source Life, Normal (hours):	1500
Light Source Life, Dynamic Eco-Mode (hours):	3500
Brightness (ANSI Lumens):	5,200
Color Depth:	30 bits, 1.07B Color (10+10+10)
Resolution:	1280 x 800
Aspect Ratio:	16:10
Resolution Type:	WXGA
Display Size (in.):	20.7 - 351.7 in. / 0.53 - 8.9m

**Video Signal:**

Frequency Horizontal:	15-100kHz
Frequency Vertical:	24-120Hz

**Compatibility:**

PC Resolution (max):	Up to 1920x1080
Mac® Resolution (max):	Up to 1920x1080

**Connector:**

USB 2.0 Type A(1), USB 2.0 Type B(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(3), Control (RS232)(1), HDMI 1.4(1), HDMI MHL(1), DVI-D(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), S-Video In(1), RCA Audio Out(1), 3D VESA(1), Wired Remote In(1), Wired Remote Out(1), 5-BNC(1)

**Audio:**

Internal Speakers:	7W (x2)
--------------------	---------

**Power:**

Voltage:	100~240VAC (Auto Switching), 50-60Hz (universal)
Consumption (max):	480W
Stand-by:	<0.5W

**Controls:**

Power, H/V lens shift, focus, zoom,
-------------------------------------

**Additional Hardware:**

Kensington Lock Slot:	1
-----------------------	---

**Weight (imperial):**

Net (lbs):	18.26
Gross (lbs):	27.31

**Weight (metric):**

Net (kg):	8.29
Gross (kg):	12.4

**Dimensions (metric) (WxHxD):**

Packaging (mm):	576 x 436 x 291
Physical (mm):	445 x 325.5 x 147.8

**Dimensions (imperial) (WxHxD):**

Packaging (in.):	576 x 436 x 291
Physical (in.):	445 x 325.5 x 147.8

**General:**

Regulations: UL, cUL, FCC, CE, EMC, CB, ROHS, REACH, SVCH, WEEE, ErP, Mexico NOM/ENERGY, PSB, RCM, CCC

PACKAGE CONTENTS: Pro9520WL projector, power cable, VGA cable, laser remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service\*\*

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907848014

**Accessories:**

HB10B, PJ-WMK-006, RLC-106, VIEWSTICK2, VIEWSYNC3
---

Physical Controls:	keystone/arrow keys, left/blank, right/panel key lock, menu/exit, mode/enter, source
On Screen Display:	Display, Image, Video, Audio, Basic, Advanced
<b>Operating Conditions:</b>	
Temperature:	41-104° F (5-40° C)
Humidity (non-condensing):	10-85%

Copyright © ViewSonic Corporation 2000-2017. All rights reserved. (01/31/2017 02:37 PM PST)